



**Shell**  
**HELIX**  
Motor oils

# SHELL HELIX MOOTORIÖLIDE SOOVITUSTABEL

AUTO MARK	BENSIINIMOOTORID	SPETSIFIKATSIOON	DIISELMOOTORID	SPETSIFIKATSIOON
	Shell Helix Ultra ECT C2/C3 0W-30	ACEA C2	Helix Ultra Professional APL 0W-30	ACEA C2; Fiat 9.55535-S1
	Shell Helix Ultra 5W-40 <sup>(1)</sup>	ACEA A3/B4	Helix Ultra ECT C2/C3 0W-30	ACEA C2; Fiat 9.55535-S1
 	Shell Helix Ultra Professional AV-L 0W-30	VW 504/507	Shell Helix Ultra Professional AV-L 0W-30	VW 504/507
	Shell Helix Ultra ECT C2/C3 0W-30 <sup>(2)</sup>	VW 504/507	Shell Helix Ultra ECT C2/C3 0W-30 <sup>(2)</sup>	VW 504/507
	Shell Helix Ultra / HX8 5W-40	VW 502/505	Shell Helix Ultra / HX8 5W-40	VW 502/505
 	Shell Helix HX8 ECT 5W-30	VW 504/507	Shell Helix HX8 ECT 5W-30	VW 504/507
			Shell Helix HX7 Professional AV 5W-30	VW 505.01
 	Shell Helix Ultra Professional AML 5W-30 <sup>(3)</sup>	BMW LL-04	Shell Helix Ultra Professional AML 5W-30 <sup>(3)</sup>	BMW LL-04
	Shell Helix Ultra ECT C3 5W-30 <sup>(3)</sup>	BMW LL-04	Shell Helix Ultra ECT C3 5W-30 <sup>(3)</sup>	BMW LL-04
	Shell Helix Ultra 5W-40 (8a. ja vanemad)	BMW LL-01	Shell Helix Ultra 5W-40 (8a. ja vanemad)	BMW LL-01
	Shell Helix HX8 ECT C3 5W-30 <sup>(3)</sup>	BMW LL-04	Shell Helix HX8 ECT C3 5W-30 <sup>(3)</sup>	BMW LL-04
 	Shell Helix Ultra Professional APL 5W-30	PSA B712290	Shell Helix Ultra Professional APL 5W-30 <sup>(4)</sup>	PSA B712290
	Shell Helix Ultra Professional APL 0W-30	PSA B712312	Shell Helix Ultra Professional APL 0W-30	PSA B712312
	Shell Helix Ultra Professional AF 5W-30	ACEA A5/B5	Shell Helix Ultra 5W-40	PSA B712296
	Shell Helix Ultra 5W-40	PSA B712296		
	Shell Helix Ultra 5W-30	API SN	Helix Ultra Professional ARL 5W-30 <sup>(5)</sup>	Renault RN0720
	Shell Helix HX7 10W-40	RENAULT RN0700		
	Shell Helix Ultra Professional AF 5W-30	ACEA A5/B5	Shell Helix Ultra ECT C2/C3 0W-30	API CF; ACEA C2/C3
	Shell Helix Ultra SN 0W-20	API SN/CF; ILSAC GF-5	Shell Helix Ultra ECT C3 5W-30	API CF; ACEA C3
	Shell Helix Ultra ECT C3 5W-30	API SN		
 	Shell Helix HX7 ECT 5W-40 <sup>(1)</sup>	ACEA C3	Helix Ultra ECT C2/C3 0W-30	ACEA C2; Fiat 9.55535-S1
  	Helix Ultra Professional AF 5W-30	Ford WSS-M2C913-C/D	Helix Ultra Professional AF 5W-30	Ford WSS-M2C913-C/D
	Helix Ultra Professional AF 5W-20 <sup>(6)</sup>	Ford WSS-M2C948-B	Helix Ultra Professional AFL 5W-30	ACEA C1; Ford WSS-M2C-934B
			Helix HX7 Professional AV 5W-30	VW 505.01
 	Shell Helix Ultra Professional AF 5W-30	ACEA A5/B5	Shell Helix Ultra Professional AV-L 0W-30	ACEA C3
	Shell Helix Ultra ECT C3 5W-30 <sup>(7)</sup>	API SN	Shell Helix Ultra/HX8 ECT C3 5W-30	ACEA C3
	Shell Helix Ultra Professional AML 5W-30	MB 229.51	Shell Helix Ultra Professional AML 5W-30 <sup>(9)</sup>	MB 229.51
	Shell Helix Ultra ECT C2/C3 0W-30	MB 229.52/229.51	Shell Helix Ultra ECT C2/C3 0W-30 <sup>(9)</sup>	MB 229.52/229.51
	Shell Helix Ultra /HX8 ECT C3 5W-30	MB 229.51/229.31	Shell Helix Ultra / HX8 ECT C3 5W-30 <sup>(9)</sup>	MB 229.51/229.31
	Shell Helix Ultra / HX8 5W-40 <sup>(8)</sup>	MB 229.5/226.5	Shell Helix Ultra / HX8 5W-40	MB 229.5/226.5
	Helix Ultra ECT C2/C3 0W-30	ACEA C2/C3	Helix Ultra Professional ARL 5W-30	ACEA C4
	Shell Helix Ultra 5W-30	API SN; ACEA B3/B4	Helix Ultra ECT C2/C3 0W-30	ACEA C2/C3
	Shell Helix Ultra Professional AG 5W-30	GM dexos 2	Shell Helix Ultra Professional AG 5W-30	GM dexos 2
	Shell Helix Ultra ECT C3 5W-30	GM dexos 2	Shell Helix Ultra ECT C3 5W-30	GM dexos 2
	Shell Helix Professional ARL 5W-30	Renault RN0720	Shell Helix Professional ARL 5W-30 <sup>(5)</sup>	Renault RN0720
	Shell Helix Ultra / HX8 5W-40	Renault RN0700/0710	Shell Helix Ultra / HX8 5W-40	Renault RN0700/0710
	Shell Helix Ultra SN 0W-20 (alates 2010)	API SN; ILSAC GF-5	Helix Ultra Professional ARL 5W-30	ACEA C4
	Shell Helix Ultra ECT C3 5W-30	API SN	Helix Ultra ECT C2/C3 0W-30	ACEA C2
 	Shell Helix Ultra SN 0W-20	API SN/CF; ILSAC GF-5	Shell Helix Ultra Professional APL 5W-30	ACEA C2
	Shell Helix Ultra ECT C3 5W-30	API SN/CF	Shell Helix Ultra ECT C2/C3 0W-30	API SN; ACEA C2/C3
	Shell Helix Ultra ECT C2/C3 0W-30	API SN; ACEA C2/C3	Shell Helix Ultra/HX8 ECT C3 5W-30	ACEA C3
	Shell Helix Ultra Professional AF 5W-30	ACEA A5/B5	Shell Helix Ultra Professional AF 5W-30	ACEA A5/B5
	Shell Helix Ultra A5/B5 0W-30	ACEA A5/B5	Shell Helix Ultra A5/B5 0W-30	ACEA A5/B5

Tabel on soovituslik, kontrollige oma autole sobilikku mootoriõli auto kasutusjuhendist või aadressilt [Lubematch.shell.com](http://Lubematch.shell.com)  
DPF: diisli kübemefilter; MY: tootmisaja; MR: vastab nõuetele

(1) Alfa Romeo 2.0 JTS, 3.2 V6 ; 2.0 T Spark; Shell Helix Ultra Racing 10W-60; Lancia Thema 3.0 ; Voyager 2.8; Shell Helix Ultra ECT C3 5W-30; Lancia Thesis 2.0, 2.4; Shell Helix Ultra Racing 10W-60; Lancia Flavia 2.4; Shell Helix Ultra SN 0W-20.

(2) V.a. mootorid R5 2.5 TDI, 5.0 V10 TDI (QG1/QG2 service, MY 2003-2006); Shell Helix Ultra Professional AV 0W30.

(3) V.a. bensiinimootorites S54 (6 silindrit), S62 (E39, E52: 8 silindrit), S65 (8 silindrit), S85 (10 silindrit) ja diiselmootor N475 (4 silindrit, kuni 09/2008), vanemad BMW M mootorid: Shell Helix Ultra Racing 10W-60.

(4) Alternatiiv diiselmootoritele ilma DPF-ta: Shell Helix Ultra 5W40.

(5) Renault G9T DPF-ga mootorites (2.2 dCi): Shell Helix Ultra 5W-40.

(6) Ühildub bensiinimootoriõlidega, mis vastavad Ford WSS-M2C925-A, Ford WSS-M2C913B/C spetsifikatsioonidele.

(7) KIA Rio III (1.25) bensiinimootorid: Shell Helix Ultra SN 0W-20.

(8) V.a. bensiinimootoris M155 (SLR).

(9) V.a. diiselmootorites OM607 (Citan), OM622 (Vito): Shell Rimula Ultra 5W30 (MB kinnitus 228.51).

(10) Kohustuslik on õige õli valikul lähtuda auto kasutusjuhendist või kasutada Shell LubeMatch-i.



# TEADLIK JUHT VALIB SHELL HELIX MOOTORIÕLI



DRIVE ON



Shell  
**HELIX ULTRA**  
with PUREPLUS Technology

JÄRGMISE PÕLVKONNA TÄISSÜNTEETILINE  
KÕRGEKVALITEEDILINE MOOTORIÕLI



**SOORITUSVÕIME**  
SUUREL MOOTORI  
KOORMUSEL



**SOORITUSVÕIME**  
**ÄÄRMUSLIKEL**  
TEMPERatuuridel



LOODUD **SUURTE**  
**VÕIMSUSTE JA KÕRGE**  
**SOORITUSVÕIME**  
SAAVUTAMISEKS

## SHELL HELIX ULTRA PÜSIB KAUEM VORMIS



ET PAKKUDA  
**ÜLIMAT**  
**KULUMISKAITSET<sup>1</sup>**



KUNI **32%** PAREM ÕLI VANANEMISKINDLUS, KUI NÕUAB  
UUSIM TÖÖSTUSHARU STANDARD<sup>2</sup>

ET KAITSTA  
**MOOTORIT ÄÄRMUSLIKEL**  
**TEMPERatuuridel**

KUNI

**50%**

VÄHEM AURUSTUMIST<sup>3</sup>



VOOLAB KUNI

**3x**

KIIREMINI<sup>2</sup> NII MADALAL TEMPERatuurIL  
NAGU -40°C, TAGADES KERGEMA KÄIVI-  
TUSE JA KIIREMA MOOTORI SOOJENEMISE



TESTID SUURTES  
AUTOPARKIDES TÕESTAVAD,  
ET SOORITUSVÕIME EI  
LANGE (KÜTUSESÄÄST JA  
VÕIMSUS) ISEGI PÄRAST  
**100,000 km**



### SOOVITAGE SHELL HELIX ULTRA-t

SUHTELISELT UUTE LUKSUS-, SPORT- VÕI KÕRGE SOORITUSVÕIMEGA AUTODE OMANIKELE  
NORMAALSETES VÕI RASKETES SÕIDUTINGIMUSTES:



**KUUMADES JA**  
**KÜLMADES**  
OLUDES



**TIHEDAS LIIKLUSES**  
PIKKI VÕI LÜHIKESI  
VAHEMAID LÄBIDES



KUI **ÕLIVAHETUST** EI OLE  
TEHTUD SOOVITATUD  
VÄLPADE TAGANT



### PUREPLUS TEHNOLOGIA

SHELL HELIX ULTRA ON KAASAEGNE,  
SÜNTEETILINE, VALMISTATUD MAAGAASIST, MIS  
TEEB TA **TUGEVAMAKS<sup>4</sup>** JA VÄHEM  
LENDUVAKS MOLEKULAARTASANDIL, VÕRRELDES  
ÕLIDEGA, MIS ON VALMISTATUD TOORNAFTAST.



USALDUS



MOOTORITOOTJATEST  
PARTNERID KASUTAVAD  
JA USALDAVAD<sup>5</sup>  
**SHELL HELIX ULTRA-t**

BMW MOTORSPORT  
HYUNDAI MOTORSPORT  
MASERATI  
SCUDERIA FERRARI

<sup>1</sup> Sequence IVA mootoritest sõltumatus laboris võrreldes API SN spetsifikatsiooniga. <sup>2</sup> Võrreldes API SN spetsifikatsiooniga. <sup>3</sup> ASTM D5800 NOACK lenduvustest.

<sup>4</sup> Põhineb parafiin süsivesinike sisaldusel ja märgatavalt kõrgemal isoparafiinide tasemel võrreldes teiste Grupp III baasõlidega. <sup>5</sup> Võidusõidupartnerid kasutavad oma võidusõiduautodes eritellimusel valmistatud Shell Helix Ultra tooteid.